

January 2006

FILLTITE READY MIXED WOOD FILLER

One Part filler is an easy to use ready mixed filler with quick drying properties. One Part filler dries to a smooth, tough crack resistant finish, is easily sandable and may be painted or stained. Suitable for both internal and external use.

- Water Based
- Non-Flammable
- Low Odour
- Non Hazardous
- Internal or External Use
- Ready for Use
- Dries white
- Quick drying

APPLICATION

Prior to application the areas must be clean, dry, sound and any traces of oil or grease must be removed. If required, use masking tape along any edges but remove within 5 minutes of application.

Apply the One Part filler firmly into the crack, gap or area of repair. Ensure no air is trapped behind. Allow to dry for 10 minutes for minor imperfections, longer times are required dependent on the filling depth. Overpaintable after drying with most solvent based and emulsion paints. If used externally, prevent contact with water for at least 5 hours.

TECHNICAL DATA

MATERIAL	-	Water based acrylic filler
MIXING RATIO	-	As supplied
DRYING:	-	1 – 8 hours depending on depth and temperature
MINIMUM APPLICATION TEMP	-	5 ° C
MAXIMUM FILL be	-	5 mm in one coat – further layers may built up
MAXIMUM DEPTH	-	25 mm

IMPORTANT

The information and data given is based on our own experience, research and testing and is believed to be reliable and accurate. However, as Tembe DIY Products Limited cannot know the varied uses to which its products may be applied, or the methods of application used, no warranty as to the fitness or suitability of its products is given or implied. It is the users responsibility to determine suitability of use. For further information please contact our Technical Department.