

INTERIOR FILLER *Le Reboucheur*



IDEAL FOR :

Filling gaps and cracks of any sizes on painted or unpainted interior substrates.



TECHNICAL FEATURES:

Will not flash or grin

Will not sink or slump

No need to spot prime

Sets in 30 mins.

No thickness limitation

Easy to rub down

Can be screwed or nailed



PACKAGING:

BOX OF 1 kg and 2KG

Bags of 5 and 10 kg (1bag incl. 10x1 unit bags).

INTERIOR



TX110 *When you want fast results*



IDEAL FOR:

Quickly and safely filling gaps and cracks of any sizes on either painted or unpainted interior substrates.



TECHNICAL FEATURES :

Can be painted within 3h

- Will not flash or grin
- Will not slump or sink
- Extra white finish
- No need to spot prime
- Sets in 30 minutes
- No thickness limitation
- Easy to rub down
- Can be screwed or nailed



Packaging :

Bags of 2, 5 or 15 kg



TOUPRELITH F *Masonry repair filler*



IDEAL FOR :

Repairing angles, Filling gaps and cracks on exterior unpainted substrates, either dry or damp.

TECHNICAL FEATURES :

Adheres even on damp masonry

Sets in 30 mns.

Will not flash or grin

Keeps its shape without formwork

Can be drilled

Fine and smooth

Easy to shape

PACKAGING :

Box of 1.5 kg / Bags of 5 and 15 kg

EXTERIOR



MUREX *All Substrates Filler*



IDEAL FOR :

Filling gaps and cracks of any sizes on dry or exterior substrates.

TECHNICAL FEATURES :

- Can be painted in 24 hours
- Exceptional Adherence**
- Will not flash or grin**
- Sets in 30 mins.
- No thickness limitation**
- Can be nailed or screwed
- Impact resistant
- Easy to shape
- White in colour

PACKAGING:

Box of 2 kg
Bags of 5 and 15 kg

EXTÉRIEUR



REDLITE *Fast drying lightweight filler*



IDEAL FOR :

Filling gaps and cracks of any sizes on painted or unpainted interior substrates.



TECHNICAL FEATURES:

- Filling in one coat
- Overcoat in 30 mins
- Will not shrink
- No sanding required
- Extra white
- No need to spot prime
- Resist to flashing and grinning

PACKAGING:

Tub of 1 L and bucket of 4 L



INTERIOR



READY MIXED FILLER *Small defects – Multi surface*



IDEAL FOR:

Filling in small cracks, shallow holes and gaps on interior substrates.

TECHNICAL FEATURES :

- Will not flash or grin
- Resists slumping
- No need to spot prime
- Easy to sand if overfilled

Packaging :

Tubs of 1,5 kg



INTERIOR



FINE SURFACE FILLER *Ready mixed*



IDEAL FOR :

Smoothing walls and ceilings and before application of painting or wallpaper coating.

TECHNICAL FEATURES :

- Ready to use
- Up to 1 mm per coat
- For walls and wood work
- Enhances paint finish
- No need to spot prime

PACKAGING:

Tubs of 1,5 kg



FIBACRYL *Flexible fiber filler for cracks treatment*

IDEAL FOR :

Exterior facade and masonry crack treatment.
Joint filling of two materials internally.

TECHNICAL FEATURES :

Enriched with fibres
Flexible after drying
Moves with the substrate without cracking.
Good adherence on paint work
Up to 10 mm per coat
No need to spot prime
Will not flash or grin

PACKAGING :

Tub of 1 kg and bucket of 5 kg.



EXTERIOR

